

VORTAC ELW

108.6

Chan 23

APP CRS

039°

Rwy Ldg

6002

TDZE

759

Apt Elev

782

VOR RWY 5

ANDERSON RGNL (A.ND)

▼

Rwy 17, 35 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use CEU altimeter setting and increase all MDAs 60 feet and S-5 visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM. VDP NA when using CEU altimeter setting. Circling Rwy 17, 35 NA at night.

MALSR

MISSED APPROACH:

Climb to 1600 then climbing left turn to 2500 direct ELW VORTAC and hold.

ASOS	GREER APP CON ★	CTAF
120.675	118.8 270.275	123.6 0

One Minute Holding Pattern

ELW VORTAC

1600

2500

ELW

6000

2500

←224°

044°→

039°

2.98 NM TCH 49

4.1 NM

1.3

ELW 4.1

ELW 5.4

CATEGORY	A	B	C	D
S-5	1200-½	441 (500-½)	1200-¾	441 (500-¾)
CIRCLING	1260-1 478 (500-1)	1320-1 538 (600-1)	1440-1¾ 658 (700-1¾)	1500-2¼ 718 (800-2¼)

ELEV 782

TDZE 759

ANDERSON, SOUTH CAROLINA

Amdt 10C 05SEP24

34°30'N-82°43'W

ANDERSON RGNL (A.ND)

VOR RWY 5