

LOC I-JVL	APP CRS	Rwy Ldg	6701
109.1	044°	TDZE	806
		Apt Elev	808

ILS or LOC RWY 4

SOUTHERN WISCONSIN RGNL (JVL)



DME required. RNP APCH - GPS.

When local altimeter setting not received, use Rockford altimeter setting and increase DA 69 feet and all MDAs 80 feet; increase S-LOC 4 Cats C/D and Circling Cats C/D ¼ SM. For inop ALS when using Rockford altimeter setting; increase S-ILS 4 all Cats visibility to ¾ SM and S-LOC 4 Cats C/D visibility to 1 ½ SM. Circling Rwy 18 NA at night. DME from JVL VOR/DME. DME use requires simultaneous reception of I-JVL and JVL VOR/DME.

MALSR

MISSED APPROACH:
Climb to 3100 direct
OTLEE and hold.

ATIS	ROCKFORD APP CON	JANESVILLE TOWER ★	GND CON	UNICOM
128.25	121.0 327.0	118.8 (CTAF) 225.4	121.65	122.95



CATEGORY	A	B	C	D
S-ILS 4	1006-½ 200 (200-½)			
S-LOC 4	1400-½ 594 (600-½)	1400-1 594 (600-1)	1400-1¼ 594 (600-1¼)	
CIRCLING	1400-1 592 (600-1)	1420-1¾ 612 (700-1¾)	1460-2 652 (700-2)	

