

WAAS CH 93832 W02A	APP CRS 023°	Rwy Ldg 3997 TDZE 342 Apt Elev 342
--	------------------------	---

RNAV (GPS) RWY 2

CAPE GIRARDEAU RGNL (CGI)


RNP APCH - GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Cairo altimeter setting and increase LPV DA to 849 feet, LNAV/VNAV DA to 905 feet, and all visibilities ¼ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D ⅓ SM, and Circling visibility Cat C/D ¼ SM. Rwy 2 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Cairo Rgnl altimeter setting.


MISSED APPROACH: Climb to 3500 direct UWALE and hold, continue climb-in-hold to 3500.

ASOS 120.55	MEMPHIS CENTER 133.65 292.15	CAPE GIRARDEAU TOWER ★ 125.525 (CTAF) 0	GND CON 124.7	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 50).

CATEGORY	A	B	C	D
LPV DA	801-1⅓ 459 (500-1⅓)			
LNAV/VNAV DA	857-1⅓ 515 (600-1⅓)			
LNAV MDA	940-1 598 (600-1)	940-1⅓ 598 (600-1⅓)		
CIRCLING	940-1 598 (600-1)	960-1 618 (700-1)	1000-1⅓ 658 (700-1⅓)	1080-2¼ 738 (800-2¼)



NC-3, 03 SEP 2026 to 01 OCT 2026

NC-3, 03 SEP 2026 to 01 OCT 2026