

LOC/DME I-ISP	APP CRS	Rwy Ldg	7006
108.3	059°	TDZE	94
Chan 20		Apt Elev	99


ILS RWY 6 (SA CAT I & II)
LONG ISLAND MAC ARTHUR (ISP)

Procedure NA when tower closed. SA CAT I: Requires specific OPSPEC, MSPEC, or LOA approval and use of HUD to DH.
SA CAT II: Reduced lighting: Requires specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown.

MALSR

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 direct CCC VOR/DME and hold.

ATIS 120.725	NEW YORK APP CON 120.05 343.75	LONG ISLAND TOWER ★ 119.3 (CTAF) 0 335.5	GND CON 135.3	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



One Minute Holding Pattern

YOSUR INT I-SP 5.9 RADAR

600 2000 CCC


1600 239° 059° 1600

GS 3.00° TCH 52

4.6 NM 97%

CATEGORY	A	B	C	D
S-ILS 6	SA CAT I RA 162/14 150 DA 244			
S-ILS 6	SA CAT II RA 111/12 100 DA 194			

SA CATEGORY I & II ILS SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED



NE-2, 03 SEP 2026 to 01 OCT 2026

NE-2, 03 SEP 2026 to 01 OCT 2026