

WAAS CH 61020 W02A	APP CRS 022°	Rwy Ldg TDZE 38 Apt Elev 42	6526
--	------------------------	---	-------------

RNAV (GPS) RWY 2

NEWPORT NEWS/WILLIAMSBURG INTL (PHF)

RNP APCH - GPS.


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Baro-VNAV and VDP NA when using ORF altimeter setting. When local altimeter setting not received, use ORF altimeter setting and increase LPV DA to 289 feet; increase LNAV/VNAV DA to 524 feet and all visibilities ½ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climb to 2000 direct PANLE and hold.

ATIS 128.65	NORFOLK APP CON 125.7 335.625	NEWPORT NEWS TOWER ★ 118.7 (CTAF) 0 257.9 348.6	GND CON 121.9 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



ELEV 42

D

TDZE 38

6000

2300

4 NM

202°

022°

GP 3.00°

TCH 60

660

1700

6 NM

3.3 NM

0.6

1.2 NM

20

25

202°

TWR

45

REIL Rwy 20 and 25

HIRL Rwy 2-20 and 7-25

CATEGORY	A	B	C	D
LPV DA	241-1 203 (200-1)			
LNAV/ VNAV DA	460-1¼ 422 (500-1¼)			
LNAV MDA	460-1 422 (500-1)		460-1¼ 422 (500-1¼)	
CIRCLING	520-1 478 (500-1)	540-1 498 (500-1)	760-2 718 (800-2)	780-2¼ 738 (800-2¼)

4 NM

Holding Pattern

NUTTY

BCOAT

SOLOC

1.8 NM to RWY 2

1.2 NM to RWY 2

2000

PANLE

NE-3, 03 SEP 2026 to 01 OCT 2026

NE-3, 03 SEP 2026 to 01 OCT 2026