

WAAS CH 45510 W25A	APP CRS 247°	Rwy Ldg 8003 TDZE 41 Apt Elev 42
--	------------------------	---

RNAV (GPS) RWY 25


NEWPORT NEWS/WILLIAMSBURG INTL (PHF)

RNP APCH - GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Baro-VNAV and VDP NA when using ORF altimeter setting. When local altimeter setting not received, use ORF altimeter setting and increase LPV DA to 289 feet; increase LNAV/VNAV DA to 564 feet and all visibilities ½ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.

⚠ MISSED APPROACH: Climb to 2000 direct JAWES and hold.

ATIS 128.65	NORFOLK APP CON 125.7 335.625	NEWPORT NEWS TOWER★ 118.7 (CTAF) 257.9 348.6	GND CON 121.9 348.6	UNICOM 122.95
-----------------------	---	--	-------------------------------	-------------------------



2000 JAWES

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

CATEGORY	A	B	C	D
LPV DA		241-¾	200 (200-¾)	
LNAV/VNAV DA		480-1¼	439 (500-1¼)	
LNAV MDA	480-1	439 (500-1)	480-1¼	439 (500-1¼)
CIRCLING	520-1 478 (500-1)	540-1 498 (500-1)	760-2 718 (800-2)	780-2 ½ 738 (800-2 ½)

ELEV 42 TDZE 41

REIL Rwy 20 and 25
HIRL Rwy 2-20 and 7-25