

WAAS CH 45815 W24A	APP CRS 243°	Rwy Ldg TDZE 1156 Apt Elev 1156
--	------------------------	---

RNAV (GPS) RWY 24

FORT DODGE RGNL (FOD)

RNP APCH


▼

▲

Baro-VNAV and VDP NA when using Webster City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1448 feet; increase LNAV/VNAV DA to 1546 feet; increase all MDAs 60 feet and LNAV Cat C/D and Circling Cat C visibility ¼ mile.

MISSED APPROACH:
Climb to 3000 direct
GEGQI and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF) 1
----------------------------	--	---------------------------------



ELEV 1156

D TDZE 1156

3000	GEGQI	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 41).			
*INAV only.					
		PUZXI	OXDAH	4 NM Holding Pattern	
				063° → 3000	
				← 243°	
				GP 3.00°	
				TCH 50	
				1.1 NM	
				3.8 NM	
				6 NM	
CATEGORY	A	B	C	D	
LPV DA	1406-1		250 (300-1)		
LNAV/VNAV DA	1504-1¼		348 (400-1¼)		
LNAV MDA	1560-1	404 (500-1)	1560-1½ 404 (500-1½)	1560-1¼ 404 (500-1¼)	
CIRCLING	1560-1 404 (500-1)	1620-1 464 (500-1)	1740-1½ 584 (600-1½)	2080-3 924 (1000-3)	

