

WAAS Ch 70312 W18A	APP CRS 183°	Rwy Ldg 4939 TDZE 1351 Apt Elev 1353
--	------------------------	---

RNAV (GPS) RWY 18


SPRINGDALE MUNI (ASG)

T DME/DME RNP 0.3 NA. Circling NA east of Rwy 18-36. When local altimeter setting not received, use Fayetteville/Drake Fld altimeter setting and increase all DA 39 feet and all MDA 40 feet; increase LPV all Cats and LNAV Cat C/D visibility $\frac{1}{8}$ mile. Circling Cat C/D visibility $\frac{1}{4}$ mile. For inoperative MALSF, increase LPV all Cats visibility to 1 mile, LNAV Cat C/D visibility to 2 miles. For inoperative MALSF when using Fayetteville/Drake Fld altimeter setting, increase LPV all Cats visibility to $\frac{1}{8}$ mile, LNAV Cat C visibility to $\frac{1}{4}$ mile. VDP NA when using Fayetteville/Drake Fld altimeter setting. Helicopter visibility reduction below $\frac{3}{4}$ SM NA.


MALSF

MISSED APPROACH:
Climb to 3800 direct
ZAVOR and hold.

AWOS-3 124.675	RAZORBACK APP CON★ 126.6 305.2	SPRINGDALE TOWER★ 118.2 (CTAF) 0	GND CON 121.6	REIL 18, 36 122.8 0	UNICOM 122.95
--------------------------	--	--	-------------------------	-------------------------------	-------------------------





ELEV 1353	D	TDZE 1351
-----------	----------	-----------



MISSED APCH FIX

ZAVOR



CATEGORY		A	B	C	D
LPV	DA	1642- ³ / ₄ 291 (300- ³ / ₄)			
LNAV/ VNAV	DA	NA			
LNAV	MDA	2080- ³ / ₄ 729 (800- ³ / ₄)	2080-1 729 (800-1)	2080-1 ⁷ / ₈ 729 (800-1 ⁷ / ₈)	
CIRCLING		2080-1 727 (800-1)		2080-2 727 (800-2)	2220-2 ³ / ₄ 867 (900-2 ³ / ₄)