

WAAS
CH **58104**
W09A

APP CRS
084°

Rwy Ldg
TDZE
Apt Elev
6701
845
845

RNAV (GPS) RWY 9L

GRAND FORKS INTL (GFK)

RNP APCH - GPS.

▼ Baro-VNAV and VDP NA when using CKN altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use CKN altimeter setting and increase LPV DA to 1106 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1156 feet and all visibilities ⅓ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 2800 direct URBH and hold.

ATIS
119.4

GRAND FORKS APP CON ★
118.1 318.1

GRAND FORKS TOWER ★
118.4 (CTAF) 350.35 (17R/35L, 9L/27R)
120.55 350.35 (17L/35R, 9R/27L)

GND CON
124.575

UNICOM
122.95

Procedure NA for arrivals at GFK VOR/DME on V55 northeast bound.

4 NM Holding Pattern

DUCEV

ARIDE

BALEE 1.6 NM to RW09L

2800 URBH

GP 3.00° TCH 45

6000 4000

2500 1400

5.8 NM 3.5 NM 0.6 1 NM

CATEGORY	A	B	C	D
LPV DA		1045-¾	200 (200-¾)	
LNAV/VNAV DA		1095-¾	250 (300-¾)	
LNAV MDA		1200-1	355 (400-1)	
CIRCLING	1260-1 415 (500-1)	1300-1 455 (500-1)	1400-1½ 555 (600-1½)	1420-2 575 (600-2)

ELEV 845 TDZE 845