

LOC/DME I-ANE
111.15
Chan **48 (Y)**

APP CRS
269°

Rwy Ldg **5000**
TDZE **910**
Apt Elev **912**

ILS or LOC RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

DME required. RADAR required for procedure entry at BLAYN.

⚠

VDP NA when using Crystal altimeter setting. When local altimeter setting not received, use Crystal altimeter setting and increase S-ILS 27 DA to 1131 feet; increase all MDAs 40 feet and S-LOC 27 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. For inop ALS when using Crystal altimeter setting, increase S-LOC 27 Cat C/D visibility to 1 ½ SM.

MALSR

MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700.

ATIS 120.625	MINNEAPOLIS APP CON 126.5 335.65	ANOKA TOWER★ 132.4 (CTAF) 0	GND CON 121.85	UNICOM 122.95
------------------------	--	---------------------------------------	--------------------------	-------------------------

Chart details include:
- **GOPHER** 117.3 GEP 117.3 Chan 120
- **LOCALIZER** 111.15 I-ANE Chan 48(Y)
- **MSA GEP 25 NM** 3500
- **Procedure NA for arrivals at STILS on V78 eastbound.**
- **ILS/LOC RWY 27** with various altitude and distance markers (e.g., 3100, 2600, 1780, 1082, 10.5, 16.7, 30.9).
- **LOCATOR** 111.15 I-ANE Chan 48(Y)
- **ILS/LOC RWY 27** with various altitude and distance markers (e.g., 3100, 2600, 1780, 1082, 10.5, 16.7, 30.9).

ELEV 912	TDZE 910	2700 GEP Use I-ANE DME when on the localizer course. JUDAL I-ANE 16.7 BOKYA I-ANE 6.2 KOGGE I-ANE 3.6 I-ANE 2.2 I-ANE 1 1780 2600 2600 269° 3100 GS 3.00° TCH 49 1.2 NM 1.4 NM 2.6 NM 10.5 NM				
81 4855 X 100 5000 X 100 TWR 36 269° HIRL Rwy 9-27 MIRL Rwy 18-36 REIL Rwys 9, 18, and 36 FAF to MAP 5.2 NM Knots 60 90 120 150 180 Min:Sec 5:12 3:28 2:36 2:05 1:44		CATEGORY	A	B	C	D
		S-ILS 27	1110-½ 200 (200-½)			
		S-LOC 27	1340-½ 430 (500-½)	1340-¾ 430 (500-¾)		
		CIRCLING	1400-1 488 (500-1)	1420-1½ 508 (600-1½)	1580-2 668 (700-2)	

MINNEAPOLIS, MINNESOTA

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

ILS or LOC RWY 27

Amdt 1 08SEP22

45°09'N-93°13'W