

WAAS CH 93618 W02A	APP CRS 017°	Rwy Ldg TDZE 372 Apt Elev 373
--	------------------------	---

RNAV (GPS) RWY 2



PERRYVILLE RGNL (PCD)

RNP APCH - GPS.

Rwy 2 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Baro-VNAV and VDP NA when using CGI altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C . When local altimeter setting not received, use CGI altimeter setting and increase LPV DA to 1223 feet and all visibility $\frac{1}{2}$ SM. Increase LNAV/VNAV DA to 1154 feet and all visibilities $\frac{1}{2}$ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D $\frac{1}{4}$ SM and Circling visibility Cat C $\frac{1}{4}$ SM.

MISSED APPROACH: Climb to 3000 direct ENGYN and hold.

AWOS-3PT 118.95	KANSAS CITY CENTER 127.475 346.275	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



4 NM Holding Pattern		ACDIV	DEGVY	JAVOV 2.6 NM to RW02	3000 ENGYN
6000 197°		3000 017°	017°	2200	1.8 NM to RW02
GP 3.00° TCH 40		2200	1240	0.8	1.8 NM
6 NM		3 NM	0.8	1.8 NM	
CATEGORY	A	B	C	D	
LPV DA	1123-2 751 (800-2)				
LNAV/VNAV DA	1054-2 682 (700-2)				
LNAV MDA	980-1 608 (700-1)	980-1 $\frac{3}{4}$ 608 (700-1 $\frac{3}{4}$)			
CIRCLING	980-1 607 (700-1)	1000-1 627 (700-1)	1260-2 $\frac{3}{4}$ 887 (900-2 $\frac{3}{4}$)	1260-3 887 (900-3)	