

WAAS

CH **93528**

W36A

APP CRS

003°

Rwy Ldg

5001

TDZE

343

Apt Elev

343

RNAV (GPS) RWY 36

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

RNP APCH-GPS.

▼

Baro-VNAV NA when using LFK altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C . When local altimeter setting not received, use LFK altimeter setting: Increase LPV DA to 598 feet; increase LNAV/VNAV DA to 680 feet; increase all MDAs 60 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM.

MALSR

AS

MISSED APPROACH: Climb to 2400 direct XOWNU and on track 356° to DRBOB and hold.

AWOS-3PT 135.625	HOUSTON CENTER 125.175 285.575	UNICOM 123.0 (CTAF) 0
----------------------------	--	---------------------------------

MISSED APCH FIX

DRBOB

357°

177°

4 NM

30 NM to ZIVIM

093°

273°

2400

ZIVIM

093°

273°

2400

ZIVIM

30 NM to ZIVIM (NoPT)

XOWNU

356°

(8)

RW36

YIRUN

1.5 NM to RW36

464 ±

(FAF) ZARAD

2100

003°

(7.3)

(IF/IAF) ZIVIM

003°

183°

HOLD

6000

2400

4 NM

4 NM Holding Pattern

ZIVIM

2400

XOWNU

2400

DRBOB

fr 356°

ZARAD

2100

YIRUN

1.5 NM to RW36

RW36

840

GP 3.00°

TCH 53

7.3 NM

3.9 NM

1.5 NM

CATEGORY		A	B	C	D
LPV	DA	543-½ 200 (200-½)			NA
LNAV/VNAV	DA	625-½ 282 (300-½)			NA
LNAV	MDA	720-½ 377 (400-½)	720-⅝ 377 (400-⅝)		NA
CIRCLING		860-1 517 (600-1)	1080-2 737 (800-2)		NA

81

5001 X 75

36

003°

REIL Rwy 18 0

MIRL Rwy 18-36 0

NACOGDOCHES, TEXAS

Orig-E 22JAN26

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

31°35'N-94°43'W

RNAV (GPS) RWY 36