

WAAS CH 49035 W27A	APP CRS 273°	Rwy Ldg 3499 TDZE 1198 Apt Elev 1198
--	------------------------	---


RNAV (GPS) RWY 27

RNP APCH - GPS.	
-----------------	--



- T** Baro-VNAV and VDP NA when using CAK altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Rwy 27 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use CAK altimeter setting and increase LPV DA to 1546 feet. Increase LNAV/VNAV DA to 1603 feet and all visibilities $\frac{1}{8}$ SM. Increase all MDAs 60 feet; and Circling visibility Cat C $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 4000 direct
IWWEB and hold,
continue climb-in-hold
to 4000.

AWOS-3 118.675	CLEVELAND APP CON★ 125.5 371.875	CLNC DEL 125.65	UNICOM 123.05 (CTAF) U
--------------------------	--	---------------------------	---



ELEV 1198		TDZE 1198
-----------	--	-----------



CATEGORY	A	B	C	D
LPV DA	1496-1	298 (300-1)		NA
RNAV/ VNAV DA	1553-1	355 (400-1)		NA
RNAV MDA	1640-1	442 (500-1)	1640-1 ³ / ₈ 442 (500-1 ³ / ₈)	NA
CIRCLING	1740-1 542 (600-1)	1800-1 602 (700-1)	1860-1 ³ / ₄ 662 (700-1 ³ / ₄)	NA