

WAAS CH 65809 W01A	APP CRS 009°	Rwy Idg TDZE 583 Apt Elev 588
--	------------------------	---


RNAV (GPS) RWY 1
LEBANON MUNI (M54)

RNP APCH - GPS.


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using XNX altimeter setting. Rwy 1 helicopter visibility reduction below ¾ SM NA. Circling NA to Rwy's 4 and 22. When local altimeter setting not received, use XNX altimeter setting: increase LPV DA to 1121 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1433 feet; increase all MDAs 40 feet and Circling Cat C visibility ½ SM.

MISSED APPROACH:
Climb to 3000 direct
LATGE and hold.

AWOS-3 118.325	NASHVILLE APP CON 118.4 360.7	UNICOM 122.725 (CTAF)
--------------------------	---	---------------------------------



4 NM Holding Pattern JOGUB				
6000 ← 189° 3000 → 009°				
GP 3.50° TCH 45				
← 3.1 NM → 3.7 NM → 1.5 NM → 0.9 NM → 2.1 NM				
CATEGORY	A	B	C	D
LPV DA	901-1 318 (400-1)			
LNAV/VNAV DA	1400-2½ 817 (900-2½)			
LNAV MDA	1400-1 817 (900-1)	1400-1¼ 817 (900-1¼)	1400-2½ 852 (900-2½)	817 (900-2½) 1520-3 932 (1000-3)
CIRCLING	1400-1¼ 812 (900-1¼)			



SE-1, 03 SEP 2026 to 01 OCT 2026

SE-1, 03 SEP 2026 to 01 OCT 2026