

WAAS

CH **45905**

W22A

APP CRS

215°

Rwy Ldg

7193

TDZE

26

Apt Elev

26

RNAV (GPS) RWY 22



PUNTA GORDA (PGD)

RNP APCH.

Baro-VNAV NA when using Page Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C. When local altimeter setting not received, use Page Fld altimeter setting and increase LPV DA to 276, LNAV/VNAV DA to 360, and all MDAs 60 feet; increase LNAV Cats C and D visibility ¼ SM, and Circling Cats C and D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct BULOW and hold.

ATIS 135,675	FORT MYERS APP CON★ 127.05 306.2	PUNTA GORDA TOWER★ 121.0 (CTAF) 0	GND CON 119.55	UNICOM 122,975
------------------------	--	---	--------------------------	--------------------------



2000

↑

BULOW

✧

VGSI and descent angles not coincident

(VGSI Angle 3.00/TCH 31).

AIRVA

2000

*LNAV only.

EGOTE

1.5 NM to RW22

DOGLE

1600

215°

1600

540°

GP 3.00°

TCH 40

1.5 NM

3.3 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	226-¾ 200 (200-¾)			
LNAV/VNAV DA	310-1 284 (300-1)			
LNAV MDA	420-1 394 (400-1)		420-1½ 394 (400-1½)	
CIRCLING	460-1 434 (500-1)	580-1 554 (600-1)	600-1½ 574 (600-1½)	740-2¼ 714 (800-2¼)