

WAAS CH 82327 W36A	APP CRS 002°	Rwy Idg TDZE 681 Apt Elev 698
--	------------------------	---

RNAV (GPS) RWY 36



JASPER COUNTY (RZL)

RNP APCH.

Baro-VNAV NA when using Knox altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C. When local altimeter setting not received use Knox altimeter setting and increase all DA 78 feet and all MDA 80 feet, increase LPV and LNAV/VNAV all Cats visibility ⅓ mile and LNAV and Circling Cat C visibility ¼ mile.
Rwy 36 helicopter visibility reduction below 1 SM NA. Circling NA to Rwy 9 and 27.

MISSED APPROACH:
Climb to 2600 direct
JITVI and hold.

AWOS-3P 119.175	CHICAGO CENTER 132.5 284.7	UNICOM 122.8 (CTAF) 0
---------------------------	--------------------------------------	---------------------------------



2600 JITVI		WUPAL		4 NM Holding Pattern	
* LNAV only.		ZOMDO			
CETEM 1.7 NM to RW36		2400		182°→ ←002° 2600	
RW36		2400		GP 3.00° TCH 40	
*1240		8.5 NM			
1.7		3.6 NM			
CATEGORY		A		B	
LPV DA		931-1 250 (300-1)		NA	
LNAV/ VNAV		947-1 266 (300-1)		NA	
LNAV MDA		1020-1 339 (400-1)		NA	
CIRCLING		1120-1 422 (500-1)		1380-1 682 (700-1)	
				1440-2¼ 742 (800-2¼)	
				NA	