

WAAS CH 58011 W18A	APP CRS 180°	Rwy Ldg 3998 TDZE 83 Apt Elev 83
--	------------------------	---

RNAV (GPS) RWY 18

JOHN H HOOKS JR MEML (M79)

RNP APCH - GPS.

NA

Rwy 18 helicopter visibility reduction below 1 SM NA. Straight-in and Circling Rwy 18 NA at night. Use Monroe altimeter setting, when not received, use Bastrop altimeter setting and increase all DA/MDA 20 feet; increase LPV all Cats visibility 1/8 SM. Baro-VNAV NA.

MISSED APPROACH:
Climb to 1600 direct
APERE and hold.

MLU ASOS
125.05

MONROE APP CON ★
126.9

UNICOM
122.8 (CTAF) **0**

4 NM

360°

180°

HOLD

6000

1700

(IF/IAF)

OGELS

1600

180°

(6.9)

(FAF)

YIGLU

ZAPOR

1.3 NM to RW18

187±

RW18

MISSED APCH FIX

APERE

360°

180°

4 NM

1600

APERE

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 50).

4 NM

Holding Pattern

360°

180°

6000

1700

GP 3.60°

TCH 59

1.3 NM

2.5 NM

6.9 NM

CATEGORY	A	B	C	D
LPV DA	448-1	365 (400-1)	NA	NA
RNAV/VNAV DA	559-1 3/8	476 (500-1 3/8)	NA	NA
RNAV MDA	480-1	397 (400-1)	NA	NA
CIRCLING	600-1	517 (600-1)	NA	NA

ELEV 83

TDZE 83

180°

81

3998 X 57.5

36

REIL Rwy 18 and 36 **0**

MIRL Rwy 18-36 **0**