

ILS or LOC RWY 27
COBB COUNTY INTL/MCCOLLUM FLD (RYY)

MISSED APPROACH: Climb to 1600 then climbing right turn to 3500 on heading 300° and on RMG VORTAC R-108 to TIPPY/RMG 11 DME and hold.



SE-4, 03 SEP 2026 to 01 OCT 2026

1600

3500

RMG R-108

TIPPY RMG 11

↑

hdg 300°

OVPEW I-RYY 13.9

RADAR

1600

3000

3500

273°

GS 300.0°

TCH 46

1.8 NM

4.3 NM

6.7 NM

1620

3000

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2

13.9

1600

3500

1.1

2.9

7.2</

Diagram of the HIRL Rwy 9-27 instrument approach chart. The chart shows a straight-in approach to runway 27. Key features include:

- Star symbol for the runway threshold.
- TWR (Tower) symbol.
- Distance of 6.295 NM to the MAP (Missed Approach Point).
- 0.7% climb gradient.
- 273° heading.
- 2 NM distance to the runway.

FAF to MAP 6.1 NM					
Knots	60	90	120	150	180
Min:Sec	6:06	4:04	3:03	2:26	2:02