

WAAS Ch 93725 W09A	APP CRS 093°	Rwy Ldg 4800 TDZE 483 Apt Elev 483
--	------------------------	---




RNAV (GPS) RWY 9

WALKER COUNTY/BEVILL FLD (JFXX)

Baro-VNAV NA when using Birmingham altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 40°C (104°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Birmingham altimeter setting and increase all DA 104 feet and all MDA 120 feet; increase LPV all Cats, LNAV Cats C/D and Circling Cat D visibility ¼ mile increase LNAV/VNAV all Cats and Circling Cat C visibility ⅓ mile.

MISSED APPROACH:
Climb to 2800 direct
SIPSY and hold.

AWOS-3PT 119.225	BIRMINGHAM APP CON 127.675 338.2	CLNC DEL 121.725	GCO 121.725	UNICOM 123.075 (CTAF) 0
----------------------------	--	----------------------------	-----------------------	--



CATEGORY	A	B	C	D
LPV DA	751-1		268 (300-1)	
LNAV/VNAV DA	952-1½		469 (500-1½)	
LNAV MDA	1040-1 557 (600-1)		1040-1½ 557 (600-1½)	
CIRCLING	1040-1 557 (600-1)	1080-1 597 (600-1)	1160-2 677 (700-2)	1360-2¾ 877 (900-2¾)