

WAAS CH 49238 W31A	APP CRS 314°	Rwy Ldg 4201 TDZE 1315 Apt Elev 1318
--	------------------------	---



RNAV (GPS) RWY 31

BLAIR EXEC (BTA)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Eppley Airfield altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Eppley Airfield altimeter setting and increase LPV and LNAV/VNAV DA to 1638 and visibility to 1½ mile all Cats, increase all MDA 80 feet and LNAV Cat C visibility to 1½ mile.

MISSED APPROACH:
Climb to 3100 direct BIKPE and hold.

AWOS-3 120.225	OMAHA APP CON 135.875 354.05	UNICOM 123.05 (CTAF) 0
--------------------------	--	----------------------------------



3100 BIKPE *LNAV only. *1 NM to RW31 RW31 JALKU 2.3 NM to RW31 EKABE 3100 1 NM 1.3 NM 3.2 NM 6.2 NM				
FALUK Holding Pattern 4 NM 134° → 4000 ← 314° GP 3.00° TCH 40				
CATEGORY	A	B	C	D
LPV DA	1564-7⁄8		250 (300-7⁄8)	NA
LNAV/VNAV DA	1564-7⁄8		250 (300-7⁄8)	NA
LNAV MDA	1640-1		326 (400-1)	NA
CIRCLING	1740-1 422 (500-1)	1780-1 462 (500-1)	1780-1½ 462 (500-1½)	NA