

ILS or LOC RWY 3

LOC I-COF

109.1

APCH CRS

027°

Rwy Idg

9008

TDZE

5

Arprt Elev

8

[USAF]

PATRICK SFB

(KCOF)

DME required

▼ *

When ALS inop, increase RVR to 40 and vis to ¾ mile.

**

When ALS inop, increase CAT AB RVR to 55, vis to 1 mile;
CAT CD vis to 1½ miles.

Circling not authorized NW of Rwy 3-21. When Rwy 29 VGSi inop, circling to Rwy 29 NA at night. When circling to Rwy 29 at night, operational VGSi required, remain on or above VGSi glidepath until threshold.

ALSF-1

MISSED APPROACH: Climb to 600, then climbing right turn to 3000 and intercept COF TACAN R-110 direct ZEVEX/COF 12 DME and hold.

ATIS ★

119.175 273.5

ORLANDO APP CON ★

126.025 281.425

TOWER ★

133.75 269.375

GND CON ★

124.35 335.8

CLNC DEL ★

118.4 289.4

1046

▲

PATRICK

Chan 97 COF

(115.0)

GEPRE

COF

1.5

333

▲

475

▲

(IF) FIGDA

COF

12

525

▲

R-207

2000

027°

207

▲

26

▲

1300

FIVMA

RADAR

COF

4.9

278

▲

JAPEK

COF

7.1

196

▲

LR-196

124

▲

80

▲

241

▲

R-110

200

▲

HOLD 8000

110°

290°

(IAF) ZEVEX

COF

12

3000

MSA

COF

2.5 NM

3000

1700

200°

350°

ELEV

8

D

TDZE

5

152

▲

109

▲

11

3993

× 200

200

▲

TWR

166

▲

027°

027°

HIRL Rwy 3-21

MIRL Rwy 11-29

FAF to MAP 3.4 NM

Knots

60

90

120

150

180

Min:Sec

3:24

2:16

1:42

1:22

1:08

3000

ZEVEX

COF

12

3000

FIGDA

Intep Lczz

COF

12

2000

JAPEK

COF

7.1

1300

FIVMA

COF

4.9

1300

RADAR

1300

COF

2.3

1300

GEPRE

COF

1.5

3000

600

3000

COF

R-110

027°

Arc

12

GS 3.00°

TCH 51

3.4 NM

0.5

CATEGORY	A	B	C	D
S-ILS 3 *	205/24	200	(200-½)	
S-LOC 3 **	460/24 455 (500-½)	460/45 455 (500-¾)		
CIRCLING ***	520-1 512 (600-1)	540-1½ 532 (600-½)	560-2 552 (600-2)	

Cocoa Beach, Florida

28° 14' N - 80° 37' W

PATRICK SFB (KCOF)

ILS or LOC RWY 3

SE-3, 01 OCT 2026 to 29 OCT 2026

SE-3, 01 OCT 2026 to 29 OCT 2026