



WAAS CH 78028 W25A	APP CRS 254°	Rwy Ldg TDZE Apt Elev	5501 3586 3662
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 25
BILLINGS LOGAN INTL (BIL)

RNP APCH - GPS.		MISSED APPROACH: Climb to 6000 direct OLOLE and on track 300° to OXIVY and hold.	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C.			
ATIS 126.3	BILLINGS APP CON 120.5 284.6	BILLINGS TOWER 127.2 257.8	GND CON 121.9



ELEV 3662	D	TDZE 3586
------------------	----------	------------------



6000 ↑		OLOLE ✧		tr 300°		OXIVY △			
		RW25 1.2 NM to RW25		FASOK 5200		MUMEE		5 NM Holding Pattern	
		1.2 NM		3.9 NM		5.9 NM		10000 6000	
				254°		074°		GP 3.00° TCH 36	
CATEGORY		A		B		C		D	
LPV DA				3836-¾ 250 (200-¾)					
LNAV/VNAV DA				3920-1 334 (300-1)					
LNAV MDA				3960-1 374 (300-1)					
CIRCLING		4160-1 498 (500-1)		4180-1½ 518 (600-1½)		4580-3 918 (1000-3)			