

RNP APCH.

RADAR required.

▼

Rwy 18 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter not received, use Port Isabel altimeter setting and increase all MDA 40 feet; increase LNAV Cats C and D visibility $\frac{1}{8}$ mile and Circling Cat D $\frac{1}{4}$ mile.

▲

MISSED APPROACH: Climb to 500 then climbing left turn to 1900 direct RELAX and hold.

ATIS 128.55	VALLEY APP CON 119.5 257.6	BROWNSVILLE TOWER ★ 118.9 (CTAF) 239.3	GND CON 121.9	UNICOM 122.95
-----------------------	--------------------------------------	--	-------------------------	-------------------------

HETUK		JINAB		500	1900	RELAX
1900		1900				
				WUREP 1.6 NM to RWY 18		
				3.00° TCH 50 560		
				6.9 NM 4.2 NM 1.6 NM		
CATEGORY	A	B	C	D		
LP MDA		360-1	340 (400-1)			
LNAV MDA		380-1	360 (400-1)			
CIRCLING	440-1 418 (500-1)	540-1 518 (600-1)	540-1½ 518 (600-1½)	680-2 658 (700-2)		

ELEV 22

TDZE 20

179°

TWR

6000 X 150

7399 X 150

36

3

3

3

MIRL Rwy 18-36

HIRL Rwy 13-31