

LOC I-GBI
108.5

APP CRS
055°

Rwy Ldg
TDZE
Apt Elev
7569
708
727

ILS or LOC RWY 5
BUFFALO NIAGARA INTL (BUF)

RADAR required for procedure entry. RNP APCH - GPS. ADF required for LOC only.

MALSR

MISSED APPROACH: Climb to 3000 direct TRAVA and hold.

D-ATIS
135.35

BUFFALO APP CON
126.15 263.125

BUFFALO TOWER
120.5 257.8

GND CON
133.2 257.8

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50).

ZOBOSO RADAR

PLAZZ GB LOM

4000

2300

2272

GS 3.00°

TCH 46

10.8 NM

4.9 NM

CATEGORY	A	B	C	D
S-ILS 5	908/18 200 (200-½)			
S-LOC 5	1060/24 352 (400-½)		1060/30 352 (400-¾)	
CIRCLING	1200-1 473 (500-1)		1220-1½ 493 (500-1½)	1340-2 613 (700-2)

ELEV 727

TDZE 708

7151 X 150

8829 X 150

32

TWR

055°

REIL Rwy 14

TDZL/RCLS Rwy 5 and 23

HIRL Rwy 5-23 and 14-32

FAF to MAP 4.9 NM					
Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

BUFFALO, NEW YORK

Amtd 18 02DEC21

42°56'N-78°44'W

BUFFALO NIAGARA INTL (BUF)

ILS or LOC RWY 5