


WAAS CH 86306 W08A	APP CRS 077°	Rwy Ldg 8679 TDZE 5344 Apt Elev 5344
--	------------------------	---

RNAV (GPS) RWY 8

CASPER/NATRONA COUNTY INTL (CPR)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 7700 direct ROVEE and via track 015° to DDY VOR/DME and hold.	
⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV N/A below -25°C or above 54°C. For inop ALS, LNAV/VNAV all Cats visibility to RVR 5500 and LNAV Cat D visibility to 1½ SM.				
ATIS 126.15	CASPER APP CON ★ 120.65 354.1	CASPER TOWER ★ 118.3 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00 / TCH 52).				
Procedure	HONED	WASPI	EBICI	RW08
Turn NA	7800	7000	6360	
GP 3.00°				
TCH 55				
	6.3 NM	2 NM	1.7 NM	1.3 NM
CATEGORY	A	B	C	D
LPV DA	5594/24		250 (300-½)	
LNAV/VNAV DA	5689/40		345 (400-¾)	
LNAV MDA	5800/24	456 (500-½)	5800/45 456 (500-¾)	5800/50 456 (500-1)
CIRCLING	5800-1	456 (500-1)	5860-1½ 516 (600-1½)	6200-2¾ 856 (900-2¾)

