

APP CRS	Rwy Ldg	9001
154°	TDZE	43
	Apt Elev	46

RNAV (RNP) Z RWY 15

CHARLESTON AFB/INTL (CHS)

▼


For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). GPS required. For inop ALSF, increase RNP 0.11 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 6000.

ALSF-2

A

MISSED APPROACH: Climb to 3000 on track 154° to SHRMP and hold.

D-ATIS 124.75	CHARLESTON APP CON 120.7 306.925	CHARLESTON TOWER 126.0 239.0	GND CON 121.9 348.6
------------------	-------------------------------------	---------------------------------	------------------------



ELEV 46

TDZE 43

154°

A

B

C

D

12

15

18

21

24

27

30

33

TWR

TIPOE

See planview for multiple IF locations.

3000

tr 154°

SHRMP

1100

154°

RW15

GP 3.00° TCH 50

3.2 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		315/24	272 (300-½)	
RNP 0.30 DA		428/45	385 (400-¾)	

AUTHORIZATION REQUIRED