


LOC/DME I-RGS 110.15 Chan 38(Y)	APP CRS 183°	Rwy Ldg TDZE 744 Apt Elev 748	ILS RWY 19R (CAT II & III) CHARLOTTE/DOUGLAS INTL (CLT)
---	------------------------	---	---

DME or RADAR required. RADAR required for procedure entry.	ALSF-2 	MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 on heading 280° and on BZM VOR/DME R-183 to STULL/BZM 46.2 DME/RADAR and hold, continue climb-in-hold to 4000.
Simultaneous approach authorized.		

D-ATIS 121.15	CHARLOTTE APP CON 128.325 (001°-119°) 120.05 (120°-295°) 134.75 (296°-360°)	257.2 (180°-359°) 307.8 (360°-179°)	CHARLOTTE TOWER 118.1 257.8 (18-36) 126.4 257.8 (1R-19L) 133.35 257.8 (1L-19R)	GND CON 121.8 348.6 (W) 121.9 348.6 (E)
-------------------------	---	--	---	---



RUDKY I-RGS 20.8 RADAR	NELLA I-RGS 17.7 RADAR	EMERS I-RGS 11.4 RADAR	WOVEN I-RGS 14.5 RADAR	JHUNT I-RGS 8.2 RADAR	AUUDD I-RGS 6.3 RADAR	STULL BZM 46.2
VGSi and ILS glidepath not coincident (VGSi Angle 2.80/TCH 65).						
7000 183° 6000 5000 4000 3000 2400 2000 1200 4000 BZM R-183 STULL BZM 46.2						
GS 3.00° TCH 55						
IM 840						
1078'						
CATEGORY	A	B	C	D		
S-ILS 19R	CAT II RA 106/12 100 DA 844					
S-ILS 19R	CAT III RVR 06					
CATEGORY II & III ILS SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED						
HIRL all Rwys REIL Rwy 18 TDZL/RCLS Rwys 1L, 1R, 19R, and 36						