

|                                                      |                        |                                                   |
|------------------------------------------------------|------------------------|---------------------------------------------------|
| LOC/DME I-XUU<br><b>110.15</b><br>Chan <b>38</b> (Y) | APP CRS<br><b>003°</b> | Rwy Ldg<br>TDZE <b>744</b><br>Apt Elev <b>748</b> |
|------------------------------------------------------|------------------------|---------------------------------------------------|

ILS RWY 1L (CAT II & III)  
CHARLOTTE/DOUGLAS INTL (CLT)

|                                                            |                                                                                                           |                                                      |                                                                                                                                                                                      |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DME or RADAR required. RADAR required for procedure entry. |                                                                                                           | ALSIF-2<br>                                          | MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 on heading 280° and on BZM VOR/DME R-184 to BUDKE/BZM 26.5 DME/RADAR and hold.                                        |
| Simultaneous approach authorized.                          |                                                                                                           |                                                      |                                                                                                                                                                                      |
| D-ATIS<br><b>121.15</b>                                    | CHARLOTTE APP CON<br><b>128.325</b> (001°-119°)<br><b>120.05</b> (120°-295°)<br><b>134.75</b> (296°-360°) | <b>257.2</b> (180°-359°)<br><b>307.8</b> (360°-179°) | CHARLOTTE TOWER<br><b>118.1</b> (18-36)<br><b>126.4</b> (1R-19L)<br><b>133.35</b> <b>257.8</b> (1L-19R)<br>GND CON<br><b>121.8</b> <b>348.6</b> (W)<br><b>121.9</b> <b>348.6</b> (E) |

