

APP CRS	Rwy Ldg	8310
133°	TDZE	478
	Apt Elev	487

RNAV (RNP) W RWY 13R


DALLAS LOVE FLD (DAL.)

▼

For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). Simultaneous approach authorized. RF required. GPS required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 3000 direct ENAVE and on track 151° to TACKE and hold.

D-ATIS 120.15	LONE STAR APP CON 124.3 282.275 (N) 125.2 343.65 (S)	LOVE TOWER 123.7 239.3	GND CON 121.75 348.6
------------------	--	---------------------------	-------------------------



ELEV 487

TDZE 478

3000

ENAVE

tr 151°

TACKE

See planview for multiple IF locations.

HEXOV

LAICH

INAPT

WUREM

RW13R

GP 3.00°

TCH 48

2100

2000

1600

1250

226°

133°

0.6 NM

1.7 NM

1.1 NM

2.3 NM

CATEGORY	A	B	C	D
RNP 0.20 DA		781/50	303 (300-1)	
RNP 0.25 DA		833/60	355 (400-1¼)	
RNP 0.30 DA		929-1½	451 (500-1½)	

AUTHORIZATION REQUIRED

TDZL/RCLS Rwy 13L and 31L
HIRL Rwy 13L-31R, and 13R-31L

SC-2, 01 OCT 2026 to 29 OCT 2026

SC-2, 01 OCT 2026 to 29 OCT 2026