




APP CRS	Rwy Ldg	10000
213°	TDZE	642
	Apt Elev	645

RNAV (RNP) U RWY 22R
DETROIT METRO WAYNE COUNTY (DTW)

RNP AR APCH.		MALSR	MISSED APPROACH: Climb to 1100 then climbing right turn to 4000 direct DOHNT and hold.
▼ For uncompensated Baro-VNAV systems, procedure NA below -19°C (-2°F) or above 54°C (130°F). Simultaneous approach authorized. For inop ALS, increase RNP 0.30 all Cats visibility to RVR 5500.			
D-ATIS	DETROIT APP CON	METRO TOWER	GND CON
133.675	124.05 284.0	135.0 317.725	121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)



1100 ↑	4000 ↗	DOHNT ✦	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).			
			EMINN	TAYUL	MMOTR	GRDCY
			ANGGL	WONDR		
			2000	3000	3000	4000
			2000	3000	4000	4000
			4.1 NM	3.1 NM	3.1 NM	3.1 NM
			3.1 NM	3.1 NM	3.1 NM	2 NM
			213°			
						GP 3.00° TCH 55
CATEGORY		A		B		C
RNP 0.30 DA		987/30		345 (400-%)		
AUTHORIZATION REQUIRED						

EC-1, 01 OCT 2026 to 29 OCT 2026

EC-1, 01 OCT 2026 to 29 OCT 2026