

WAAS CH 99527 W24A	APP CRS 242°	Rwy Ldg 7799 TDZE 955 Apt Elev 955
--	------------------------	---

RNAV (GPS) RWY 24

ELMIRA/CORNING RGNL (ELM)

T
A
-21°C

Circling Rwy 10 NA at night. Circling NA for Cat D south of Rwy 10-28. Circling NA to Rwy 5 and 23. DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). When local altimeter setting not received, use Penn VNA altimeter setting and increase all DA 73 feet and all MDA 80, and increase LPV all Cats and LNAV Cats C/D visibility 1/4 mile and LNAV/VNAV all Cats visibility 1/2 mile; inop table does not apply to LNAV/VNAV all Cats; for inop MALSR, increase LPV DA** all Cats visibility to 7/8 and LPV all Cats visibility to 1/2. Baro-VNAV and VDP NA when using Penn VNA altimeter setting. For inop MALSR, increase LNAV Cats C/D visibility to 2 1/2 mile. ** Missed approach requires a minimum climb of 260 feet per NM to 2300. ** RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Penn VNA altimeter setting.

MALSR
A5


MISSED APPROACH:
Climb to 4000 direct
UNOLY and hold.

ATIS 125.475	ELMIRA APP CON★ 128.425 257.8	ELMIRA TOWER ★ 121.1 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
------------------------	---	---	-------------------------	-------------------------

MISSED APCH FIX
UNOLY



062°
242°
4 NM



ELEV 955	D	TDZE 955
----------	----------	----------

