

WAAS CH 93609 W05A	APP CRS 050°	Rwy Ldg 11981 TDZE 815 Apt Elev 815
--	------------------------	--

RNAV (GPS) RWY 5

FORT WAYNE INTL (FWA)

▼

ASR

For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cat C/D/E visibility to 1¾ SM.


ALS-F-2

ⓘ

⌵

MISSED APPROACH:
Climb to 3000 direct
SLYDR and hold.

ATIS 121.25 360.825	FORT WAYNE APP CON 127.2 284.6	FORT WAYNE TOWER 119.1 269.325	GND CON 121.9 348.6
-------------------------------	--	--	-------------------------------



4 NM
Holding Pattern

EBACO

3000

230°

050°

GP 3.00°
TCH 55

ZANOX

2500

050°

3000

SLYDR

* 1.4 NM
to RW05

RW05

* LNAV only.

6.1 NM

3.7 NM

1.4 NM

CATEGORY	A	B	C	D	E
LPV DA	1065/18 250 (300-½)				
LNAV/VNAV DA	1275/60 460 (500-1¼)				
LNAV MDA	1300/24	485 (500-½)	1300/50 485 (500-1)		
CIRCLING	1300-1	485 (500-1)	1420-1¾ 605 (700-1¾)	1520-2¼ 705 (800-2¼)	1520-2½ 705 (800-2½)

ELEV 815

TDZE 815

TDZL/RCLS Rwy 5
REIL Rwys 14 and 23
HIRL Rwys 5-23 and 14-32