

ILS or LOC RWY 28C  
CHICAGO O'HARE INTL (ORD)

MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 on heading 215° and DPA VOR/DME R-082 to DPA VOR/DME and hold.

**T** Simultaneous approach authorized.

113.0 OBK  
Chan 77

R-166

SEIKA INT  
I-VZE [7]  
RADAR

HAZIL  
I-VZE [12.7]  
RADAR

(IF)  
RZUKO  
I-VZE [15.8]  
RADAR

MEMAW  
I-VZE [19]  
RADAR

KOENN  
I-VZE [22.1]  
RADAR

SNTOE  
I-VZE [25.3]  
RADAR

INDUH  
I-VZE [28.4]  
RADAR

(IAF)  
VOGLR

2300  
4000  
5000  
6000  
7000  
8000  
9000

273°  
273°

(5.7)  
(3.1)  
(3.1)  
(3.1)  
(3.1)  
(3.1)

093°

277° (17.2)

771

IM

114.55 DPA  
R-082  
Chan 92Y

ZUPTI INT  
I-VZE [3.8]

LOCALIZER 108.95  
I-VZE [3.8]  
Chan 26 (Y)

MSA ORD 25 NM  
3400

MISSED APCH FIX  
DUPAGE  
DPA [3.8]  
114.55  
Chan 92Y  
R-248-068°  
248°

ELEV 680  
TDZE 651

|                                                         |                                 |                                |                                |                                |                                |
|---------------------------------------------------------|---------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
|                                                         | DPA<br>R-082                    | DPA<br>                        | RZUKO<br>I-VZE [15.8]<br>RADAR | KOENN<br>I-VZE [22.1]<br>RADAR | LNDUH<br>I-VZE [28.4]<br>RADAR |
| * LOC only.                                             |                                 |                                |                                |                                |                                |
| I-VZE [2]<br>IM                                         | SEIKA INT<br>I-VZE [7]<br>RADAR | HAZIL<br>I-VZE [12.7]<br>RADAR | MEMAW<br>I-VZE [19]<br>RADAR   | SNTOE<br>I-VZE [25.3]<br>RADAR | 273° 9000                      |
| * I-VZE [2.9]                                           | ZUPTI INT<br>I-VZE [3.8]        | 2300                           | 5000                           | 7000                           | 8000                           |
| 0.1 0.9 0.8                                             | * 1200                          | 2300                           | 4000                           | 5000                           | 6000                           |
| 0.1 0.9 0.8                                             | 3.2 NM                          | 5.7 NM                         | 3.1 NM                         | 3.1 NM                         | 3.1 NM                         |
| CATEGORY                                                | A                               | B                              | C                              | D                              |                                |
| S-ILS 28C                                               | 851/18                          | 200 (200-½)                    |                                |                                |                                |
| S-LOC 28C                                               | 1200/24                         | 549 (600-½)                    | 1200/60                        | 549 (600-1¼)                   |                                |
| ZUPTI FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED) |                                 |                                |                                |                                |                                |
| S-LOC 28C                                               | 1040/24                         | 389 (400-½)                    | 1040/35                        | 389 (400-¾)                    |                                |