

WAAS CH 70643 W27D	APP CRS 273°	Rwy Ldg 11245 TDZE 653 Apt Elev 680
--	------------------------	--

RNAV (GPS) RWY 27C



CHICAGO O'HARE INTL (ORD)

RNP APCH.
Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to RVR 6000.

ALS-2

MISSED APPROACH:
Climb to 1100 then climbing right turn to 4000 direct UKUNE and hold.

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 121.15 348.0	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)
--------------------------------	---	-------------------------------------	---	---



1100	4000	UKUNE	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 75).		NCHLS
					9000
*LNAV only.					
	YVONE 1.4 NM to RW27C	DRSCL 2200	JMBBO 4000	MRRFF 5000	BOOWW 6000
	RW27C	1160*	2200		
	1.4	3.3 NM	→ 6 NM →	3.1 NM	3.1 NM
CATEGORY	A	B	C	D	
LPV DA	853/18		200 (200-½)		
LNAV/VNAV DA	1086/40		433 (500-¾)		
LNAV MDA	1060/24		1060/40		407 (400-¾)