


WAAS CH 99508 W09B	APP CRS 093°	Rwy Ldg 7500 TDZE 668 Apt Elev 680
--	------------------------	---

RNAV (GPS) RWY 9L

CHICAGO O'HARE INTL (ORD)


RADAR required for procedure entry. RNP APCH.			ALSIF-2 	MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct OBK VOR/DME and hold, continue climb-in-hold to 4000.
Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -19°C or above 54°C.				
D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 128.15 348.0	GND CON (TWR CENTER) 124.125 (TWR NORTH) 121.75 (OBND) 118.05 (TWR SOUTH) 121.9 (IBND) 226.675 (ALL TWRs)	



JHONN		ESSSS		VNDER		ILUUM		TRYXI		ZENAH		OGSIE 3.3 NM to RW09L		*LNAV only.	
9000		8000		7000		6000		5000		4000		2300		*1760	
GP 3.00° TCH 55														RW09L	
→ 3.1 NM		3.1 NM		3.1 NM		3.1 NM		3.1 NM		5.5 NM		1.7 NM		2.1 1.2	
CATEGORY															
LPV DA	868/18 200 (200-½)														
LNAV/ VNAV DA	1034/35 366 (400-¾)														
LNAV MDA	1100/24 432 (500-½) 1100/40 432 (500-¾)														

ELEV 680 TDZE 668

093°



HIRL all rwys
TDZL/RCLS all rwys except 4L