

WAAS CH 56214 W36A	APP CRS 357°	Rwy Ldg 12901 TDZE 1175 Apt Elev 1219
--	------------------------	--


RNAV (GPS) RWY 36
LINCOLN (LNK)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above -54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Barometric altimeter setting and increase all DA 91 feet, all MDA 100 feet and LNAV/VNAV all Cats, LNAV Cat C and D, and Circling Cats C and D visibility ¼ mile and LPV all Cats visibility ½ mile. For inop MALSR increase LPV all Cats visibility to 1 mile. For inop MALSR when using Barometric altimeter setting increase LPV all Cats visibility to 1½ mile. Baro-VNAV and VDP NA when using Barometric altimeter setting.




MISSED APPROACH:
Climb to 3800 direct
AYARE and hold.

ATIS 118.05 290.9	OMAHA APP CON 124.0 270.3	LINCOLN TOWER ★ 118.5 (CTAF) 253.5	GND CON 121.9 275.8	UNICOM 122.95
----------------------	------------------------------	---------------------------------------	------------------------	------------------



ELEV 1219	D	TDZE 1175
MIRL Rwy 14-32 and 17-35 REIL Rwy 14 and 17 HIRL Rwy 18-36		



4 NM Holding Pattern

GONBE

JUDAD

2800

3800

AYARE

177°

357°

357°

2800

1.2 NM to RW36

*LNAV only

GP 3.00°

TCH 56

6 NM

3.7 NM

1.2 NM

RW36

CATEGORY	A	B	C	D
LPV DA	1493/24		318 (300-½)	
LNAV/VNAV DA	1669/60		494 (500-1¼)	
LNAV MDA	1620/24 445 (500-½)		1620/40 445 (500-¾)	1620/50 445 (500-1)
CIRCLING	1720-1 501 (600-1)	1760-1 541 (600-1)	1820-1¾ 601 (700-1¾)	1960-2½ 741 (800-2½)

RNAV (GPS) RWY 36