

APP CRS
350°

Rwy Ldg
TDZE
Apt Elev

10000
464
501

RNAV (RNP) Z RWY 35L

LOUISVILLE MUHAMMAD ALI INTL (SDF')

RNP AR APCH - GPS.

T

For uncompensated Baro-VNAV systems, procedure NA below -10°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.11 all Cats visibility to RVR 4500.

ALS-F2

A

MISSED APPROACH: Climb to 1000 then climbing left turn to 4000 direct DAMEN and hold.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6
-------------------	-------------------------------------	---------------------------------	------------------------

MISSED APCH FIX

4 NM

279°

099°

DAMEN

ROUTING TO AWLEE (not to scale)

(IF) AWLEE 210K

4000

(3.5)

RDBRD 210K

350°

(4.1)

(IAF) BRBON 6000

5000

350°

(IF) AABEY 6000 210K

Procedure NA for arrivals at BRBON on V5-513 southbound.

350°

(5.9)

RW35L

(FAF) CRDNL

2400

(5.4)

BEEPO 190K

4000

(1.35)

(IF) DPAUW 6000 210K

2400

(9.3)

MUGNZ

5300

(4.8)

(IF) AABEY 6000 210K

3600

MSA RW35L 25 NM

ELEV 501

TDZE 464

7251 X 150

11887 X 150

35L

35R

TWR

HIRL all Rwys TDZL/RCLS Rwys 17L, 17R, 35L and 35R

R-3704 A & B

1000

4000

DAMEN

SEE INSET FOR ROUTING TO AWLEE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).

CRDNL 2400

GP 3.00° TCH 59

See planview for multiple IF locations.

5.9 NM

CATEGORY	A	B	C	D
RNP 0.11 DA	769/24	305 (300-½)		
RNP 0.30 DA	897/40	433 (400-¾)		

AUTHORIZATION REQUIRED

LOUISVILLE, KENTUCKY

Amdt 2 11JUL24

38°10'N-85°44'W

LOUISVILLE MUHAMMAD ALI INTL (SDF')

RNAV (RNP) Z RWY 35L