


WAAS CH 97315 W05A	APP CRS 054°	Rwy Ldg TDZE 344 Apt Elev 354
--	------------------------	---

RNAV (GPS) RWY 5

MIDDLE GEORGIA RGNL (MCN)

RNP APCH. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C.		MALSR 	MISSED APPROACH: Climb to 2600 direct IPJOM and hold.	
ATIS 120.775	ATLANTA APP CON ★ 124.2 279.6	MACON TOWER ★ 128.2(CTAF) 257.8	GND CON 121.65	UNICOM 122.95



4 NM Holding Pattern		BLSKY	2600	IPJOM
6000 ← 234°		ALLMN	2000	BRROS 2.2 NM to RWY05
2600 → 054°		2000	*1080	*1.5 NM to RWY05
GP 3.00°		5.9 NM	2.9 NM	0.7 NM
TCH 56				1.5 NM
CATEGORY	A	B	C	D
LPV DA	544/24		200 (200-½)	
LNAV/VNAV DA	863-1⅜		519 (600-1⅜)	
LNAV MDA	860/24	516 (600-½)	860/55	516 (600-1)
CIRCLING	900-1	546 (600-1)	920-1½ 566 (600-1½)	1120-2½ 766 (800-2½)

