

LOC I-CID 109.3	APP CRS 089°	Rwy Ldg TDZE 857 Apt Elev 869
---------------------------	------------------------	---


ILS or LOC RWY 9
THE EASTERN IOWA (CID)

⚠ When local altimeter setting not received, use Iowa City altimeter setting and increase all DA 64 feet and all MDA 80 feet; increase S-LOC Cat C visibility to RVR 4000 and Cat D to RVR 6000. OPHAW fix minimums: increase S-LOC Cat C visibility to RVR 4000 and Cat D to RVR 6000. When using Iowa City altimeter setting, for inop MALSR, increase S-ILS 9 all Cats visibility to RVR 5000. Autopilot coupled approach NA below 1100 MSL. # RVR 1800 authorized with use of FD or HUD to DA (NA when using Iowa City altimeter setting).

MALSR

MISSED APPROACH: Climb to 1400 then climb to 2700 via CID VOR/DME R-082 to LISBO/CID VOR/DME 19.1 DME and hold.

ATIS 124.15	CEDAR RAPIDS APP CON★ 119.7 266.8	CEDAR RAPIDS TOWER★ 118.7 (CTAF) 266.8	GND CON 121.6	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



ELEV **869** **D** TDZE **857**

HIRL Rwy 9-27 **1**
MIRL Rwy 13-31 **1**
REIL Rwy 13

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

⚠ 1440 when using Iowa City altimeter setting. Remain within 10 NM

GS 3.00° TCH 49 VGSi and ILS glidepath not coincident (VGSi Angle 3.00/TCH 60).

***1360**

*1440 when using Iowa City altimeter setting. Remain within 10 NM 2500 269° 2500 089° 2500 GS 3.00° TCH 49 VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 60). FONER INT CID 2.4 CID VOR/DME 2500 OPHAW CID 0.9 *LOC only CID 2.5 3.3 NM 1.7 NM 1400 2700 CID R-082 USBO Δ				
CATEGORY	A	B	C	D
S-ILS 9#	1057/24 200 (200-½)			
S-LOC 9	1360/24 503 (500-½)		1360/50 503 (500-1)	
OPHAW FIX MINIMUMS				
S-LOC 9	1220/24 363 (400-½)			1220/40 363 (400-¾)

NC-3, 01 OCT 2026 to 29 OCT 2026

NC-3, 01 OCT 2026 to 29 OCT 2026