

WAAS CH 77603 W09A	APP CRS 089°	Rwy Ldg TDZE Apt Elev 869	8175 857 869
--	------------------------	--	---


RNAV (GPS) RWY 9
THE EASTERN IOWA (CID)

⚠ Baro-VNAV NA when using Iowa City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. When local altimeter setting not received use Iowa City altimeter setting: increase LPV DA to 1121 feet; increase LNAV/VNAV DA to 1268 feet and all visibilities to RVR 5000; increase all MDA 80 feet; LNAV Cat C visibility to RVR 4000, and Circling Cat C and D visibility ¼ SM. For inop MALSRS increase LNAV Cat D visibility to RVR 6000. VDP NA with Iowa City altimeter setting. When using Iowa City altimeter setting; for inoperative MALSRS, increase LPV all Cats visibility to RVR 5000, LNAV Cat C visibility to RVR 6000 and LNAV Cat D visibility to 1½ miles.
RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Iowa City altimeter setting.


MALSRS

MISSED APPROACH:
Climb to 2700 direct JUTUS and hold.

ATIS 124.15	CEDAR RAPIDS APP CON ★ 119.7 266.8	CEDAR RAPIDS TOWER ★ 118.7 (CTAF) 0 266.8	GND CON 121.6	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 60).					2700 	JUTUS 
4 NM Holding Pattern CUKLA FONER OPHAW 1.7 NM to RW09 *1 NM to RW09 RW09 *LNAV only						
2500 ← 269° 089° → 2500 GP 3.00° TCH 49 2500 *1440 6.1 NM 3.3 NM 0.7 NM 1 NM						
CATEGORY	A	B	C	D		
LPV DA#	1057/24 200 (200-½)					
LNAV/VNAV DA	1204/40 347 (400-¾)					
LNAV MDA	1240/24 383 (400-½)				1240/50 383(400-1)	
CIRCLING	1280-1 411 (500-1)	1320-1 451 (500-1)	1560-2 691 (700-2)	1560-2¼ 691 (700-2¼)		



NC-3, 01 OCT 2026 to 29 OCT 2026

NC-3, 01 OCT 2026 to 29 OCT 2026