



LOC/DME I-MFR	APP CRS	Rwy Ldg	8800
110.3	143°	TDZE	1303
Chan 40		Apt Elev	1335

ILS or LOC RWY 14

ROGUE VALLEY INTL/MEDFORD (MFR)

DME required. DME or RADAR required for procedure entry.		MALSR	MISSED APPROACH: Climb to 6600 on I-MFR SE course to JLOK/I-MFR 1.6 DME and climbing right turn on heading 350° and on OED VORTAC R-160 to OED VORTAC and hold, continue climb-in-hold to 6600. #Missed approach requires minimum climb of 331 feet per NM to 4100.
Circling NA for Cats C and D northeast of Rwy 14-32. When Medford altimeter setting not received, procedure NA. For inop ALS, increase S-ILS 14 visibility to 1½ SM, increase S-LOC 14# Cats C and D visibility to RVR 5500, increase S-LOC 14 Cats C and D visibility to 2½ SM.			
ATIS	CASCADE APP CON	MEDFORD TOWER	GND CON
127.25	124.3 379.9	119.4 (CTAF) 0 257.8	121.8
		UNICOM	122.95



VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 73).				6600	JLOK I-MFR 1.6	OED R-160	OED
S-ILS 14				7000	5700	4600	3900
S-LOC 14#				143°	143°	143°	143°
S-LOC 14				GS 3.00° TCH 58	3900	2660	3900
CATEGORY				A	B	C	D
S-ILS 14				1503/18	200 (200-½)		
S-LOC 14				1929-1¾	626 (600-1¾)		
S-LOC 14#				1680/24	377 (400-½)	1680/35	377 (400-¾)
S-LOC 14				2080/24	2080/40	2080-1¾	777 (800-1¾)
CIRCLING				2080-1	2080-1¼	2080-2½	2340-3
				745 (800-1)	745 (800-1¼)	745 (800-2½)	1005 (1100-3)