

WAAS CH 62828 W14A	APP CRS 146°	Rwy Ldg TDZE Apt Elev 705
--	------------------------	--

RNAV (GPS) RWY 14


ST PAUL DOWNTOWN HOLMAN FLD (STP)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). Rwy 14 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV Cats C and D to 2½ SM.

MALSR

MISSED APPROACH: (Do not exceed 250K until WHISK) Climb to 1700 then climbing left turn to 3000 direct WHISK and hold.

ATIS 118.35	MINNEAPOLIS APP CON 121.2 335.65	ST. PAUL TOWER ★ 119.1(CTAF) 257.8	GND CON 121.675	UNICOM 122.95
-----------------------	--	--	---------------------------	-------------------------



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 50).				
TEPAW MRANN 3000 2900 1700 3000 WHISK GP 3.00° TCH 42 5 NM 4.4 NM 2.4 NM RWY 14 * 2.4 NM to RWY 14 * LNAV only.				
CATEGORY	A	B	C	D
LPV DA	955/40		250 (300-¾)	
LNAV/VNAV DA	1511-2½		806 (900-2½)	
LNAV MDA	1520/40	815 (900-¾)	1520-1⅞	815 (900-1⅞)
CIRCLING	1580-1¼	875 (900-1¼)	1580-2½ 875 (900-2½)	1580-2¾ 875 (900-2¾)

ELEV 705

D

TDZE 705

146°

4004 X 150

3642 X 100

8491 X 150

TWR

MIRL Rwy 9-27

REIL Rwy 31

REIL Rwy 32

HIRL Rlys 14-32 and 13-31