

MINNEAPOLIS DEP CON
124.7 284.7 (S/E)
125.75 284.7 (N/W)
D-ATIS DEP
120.8
CLNC DEL
133.2
CPDLC

RADAR required.

**TOP ALTITUDE:
ASSIGNED BY ATC**

Rwy 17
Assigned heading 230° CW 285°
3500

Rwys 30L/R
Assigned heading 220° CW 360°
3500

MINNEAPOLIS
115.3 MSP
Chan 100

FLYING CLOUD
117.7 FCM
Chan 124

Rwys 12L/R
Assigned heading 060° CW 100°
3500

FARMINGTON
115.7 FGT
Chan 104

HALFWAY
111.2 FOW
Chan 49

REDWOOD FALLS
113.3 RWF
Chan 80

TAKEOFF MINIMUMS

Rwys 12R, 17, 22: Standard.

Rwy 4: Standard with minimum climb of 202' per NM to 2400.

Rwy 12L: Standard with minimum climb of 277' per NM to 1100.

Rwy 30L: Standard with minimum climb of 208' per NM to 2000.

Rwy 30R: Standard with minimum climb of 217' per NM to 2000.

Rwy 35: Standard with minimum climb of 219' per NM to 2100.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION	
<u>TAKEOFF ALL RUNWAYS:</u> Climb on assigned heading for RADAR vectors to assigned fix on MSP R-232, then on depicted route to SCHEP, then on transition. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure. <u>ALL AIRCRAFT: ATC CROSSING RESTRICTIONS AND CLIMB GRADIENTS:</u> If unable to accept crossing restrictions and climb rates, advise ATC prior to taxi. <u>RUNWAYS 12L/12R:</u> For assigned headings from 060° clockwise to 100°, cross MSP 7 DME Arc at or above 3500, RWY 12L: 540 feet per NM to 3500, RWY 12R: 542 feet per NM to 3500. <u>RUNWAY 17:</u> For assigned headings from 230° clockwise to 285°, cross MSP 7 DME Arc at or above 3500, 512 feet per NM to 3500. <u>RUNWAYS 30L/R:</u> For assigned headings from 220° clockwise to 360°, cross MSP 7 DME Arc at or above 3500, 380 feet per NM to 3500. <u>RXANN TRANSITION (SCHEP1.RXANN):</u> From over SCHEP INT on MSP R-232 to RXANN INT.	

NC-1, 01 OCT 2026 to 29 OCT 2026

NC-1, 01 OCT 2026 to 29 OCT 2026