

LOC I-DLV

108.5

APP CRS

277°

Rwy Ldg

9020

TDZE

197

Apt Elev

232

ILS Y or LOC RWY 28

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

⚠

For inop ALS, increase S-ILS 28 Cat E visibility to ¾ SM; S-LOC 28 Cat C/D/E visibility to 1 ¾ SM and increase WITBI fix minimums S-LOC 28 Cat E visibility to 1 ¼ SM. Circling for Cat E NA north of Rwy 10-28.

MAISLR

MISSED APPROACH: Climb to 700 then climbing left turn to 3000 direct MGM VORTAC and hold, continue climb-in-hold to 3000 (TACAN aircraft continue climb to 3500 on MGM VORTAC R-126 to SHADY/MGM 1.5 DME and hold SE, RT, 306° inbound).

ATIS 120.675	MONTGOMERY APP CON★ 124.0 363.025	DANNELLY TOWER★ 119.7 (CTAF) 360.85	GND CON 121.7 348.6	UNICOM 122.95
-----------------	--------------------------------------	--	------------------------	------------------

Diagram illustrating the ILS Y or LOC RWY 28 approach for Montgomery Regional (Dannelly Field) (MGM). The diagram shows the approach path, including the Localizer (LOC) and Glide Slope (GS) segments, and the final approach segment. Key altitudes and distances are marked, such as 2000, 2100, 2200, 2300, 2400, 2500, 2600, 2700, 2800, 2900, 3000, 3100, 3200, 3300, 3400, 3500, 3600, 3700, 3800, 3900, 4000, 4100, 4200, 4300, 4400, 4500, 4600, 4700, 4800, 4900, 5000, 5100, 5200, 5300, 5400, 5500, 5600, 5700, 5800, 5900, 6000, 6100, 6200, 6300, 6400, 6500, 6600, 6700, 6800, 6900, 7000, 7100, 7200, 7300, 7400, 7500, 7600, 7700, 7800, 7900, 8000, 8100, 8200, 8300, 8400, 8500, 8600, 8700, 8800, 8900, 9000, 9100, 9200, 9300, 9400, 9500, 9600, 9700, 9800, 9900, 10000. The diagram also shows the location of the VORTAC station, the TWR, and the MSA (Minimum Safe Altitude) for the area.

ELEV 232

TDZE 197

REIL Rwy 3

MIRL Rwy 3-21

HIRL Rwy 10-28

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

700

3000

MGM

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 75).

TEBOC INT RADAR

6000

2000

097°

277°

2000

700

1.5 NM

4 NM

GS 3.00° TCH 56

Remain within 10 NM

CATEGORY	A	B	C	D	E
S-ILS 28	397-1/2 200 (200-1/2)				
S-LOC 28	700-1/2	503 (500-1/2)	700-1	503 (500-1)	
CIRCLING	700-1	468 (500-1)	800-1 1/2 568 (600-1 1/2)	860-2 628 (700-2)	860-2 1/4 628 (700-2 1/4)
WITBI FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)					
S-LOC 28	620-1/2	423 (400-1/2)	620-3/4	423 (400-3/4)	
CIRCLING	700-1	468 (500-1)	800-1 1/2 568 (600-1 1/2)	860-2 628 (700-2)	860-2 1/4 628 (700-2 1/4)

MONTGOMERY, ALABAMA

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

Amdt 11D 20FEB25

32°18'N-86°24'W

ILS Y or LOC RWY 28