



WAAS CH 49013 W20D	APP CRS 201°	Rwy Ldg TDZE 551 Apt Elev 599
--	------------------------	---

RNAV (GPS) Y RWY 20L

NASHVILLE INTL (BNA)

RNP APCH - GPS.	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. *RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 1300, then climbing left turn to 4000 direct LENON and hold.
-----------------	---	-----------	---

D-ATIS 135.1	NASHVILLE APP CON 118.4 360.7 (030°-196°) 119.35 372.0 (197°-029°)	NASHVILLE TOWER 118.6 257.8	GND CON 121.9 348.6
------------------------	--	---------------------------------------	-------------------------------



1300	4000	LENON	JUDD	CRAMR	WAYLN
			2000	2000	4000
			1.2 NM to RW20L	2 NM to RW20L	
			1.2 NM	0.8 NM	2.5 NM
			3.2 NM	3.2 NM	
CATEGORY	A	B	C	D	
LPV DA*		751/24	200 (200-½)		
LNAV/VNAV DA		879/26	328 (300-½)		
LNAV MDA	980/24	429 (400-½)	980/40	429 (400-¾)	
CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)	