

WAAS CH 93713 W02D	APP CRS 021°	Rwy Ldg TDZE 590 Apt Elev 599
--	------------------------	---

RNAV (GPS) Y RWY 2R

NASHVILLE INTL (BNA)

RNP APCH - GPS.

T


A

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For inop ALS increase LNAV/VNAV visibility all Cnts to RVR 5500.

ALSF-2

MISSED APPROACH: Climb to 1300, then climbing right turn to 4000 direct LENON and hold.

D-ATIS 135.1	NASHVILLE APP CON 118.4 360.7 (030°-196°) 119.35 372.0 (197°-029°)	NASHVILLE TOWER 118.6 257.8	GND CON 121.9 348.6
------------------------	--	---------------------------------------	-------------------------------



LOUDN	UNIVE	SKAGS	KOYER	LENON
4000	3000	2500	1600	1300
GP 3.00° TCH 55				
3.3 NM	2.4 NM	2.8 NM	1.8 NM	1.2 NM
GP 3.00° TCH 55				
CATEGORY	A	B	C	D
LPV DA	790/18	200 (200-½)		
LNAV/VNAV DA	959/35	369 (400-¾)		
LNAV MDA	1020/24	430 (500-½)	1020/40	430 (500-¾)
CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)

