

WAAS CH 73012 W08A	APP CRS 074°	Rwy Ldg TDZE 1486 Apt Elev 1497
--	------------------------	---

RNAV (GPS) RWY 8

EASTERN OREGON RGNL AT PENDLETON (PDT)

RNP APCH.


▼
▲

Circling to Rwy 11 NA at night. Baro-VNAV and VDP NA when using Walla Walla altimeter setting. Rwy 8 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Inop table does not apply to LPV all Cats and LNAV Cats C/D. When local altimeter setting not received, use Walla Walla altimeter setting and increase all DA 122 feet and all visibilities ¼ SM. Increase all MDA 140 feet and LNAV Cat C/D and Circling Cat C visibilities ¼ SM and Circling Cat D ½ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM. For inop ALS when using Walla Walla altimeter setting, increase LNAV/VNAV all Cats visibility to 1 ½ SM.

ODALS

MISSED APPROACH:
Climb to 2100 then climbing left turn 5000 to ZUTED and hold.

ASOS 118.325	SPOKANE APP CON * 133.15 379.15	PENDLETON TOWER * 119.7 (CTAF) 257.8	GND CON 121.9 257.8	UNICOM 122.95
------------------------	---	--	-------------------------------	-------------------------



5 NM Holding Pattern

EFAKE

6000 ← 254°

4300 → 074°

GP 3.00°
TCH 56

3400

074°

CIMAG

3400

CESMI
2 NM to RW08

*1 NM to RW08

RW08

*2180

6.8 NM

3.8 NM

1

1

2100

5000

ZUTED

*LNAV only

CATEGORY

A

B

C

D

LPV DA

1736-¾

250 (300-¾)

LNAV/VNAV DA

1769-¾

283 (300-¾)

LNAV MDA

1860-¾

374 (400-¾)

1860-1

374 (400-1)

CIRCLING

1920-1

1960-1

1980-1½

2200-2¼

423 (500-1)

463 (500-1)

483 (500-1½)

703 (800-2¼)

REIL Rwy 11 and 29

MIRL Rwy 11-29

HIRL Rwy 8-26