

LIBERTY VISUAL RWY 27L

PHILADELPHIA INTL (PHL)
PHILADELPHIA, PENNSYLVANIA

D-ATIS 133.4
PHILADELPHIA APP CON
124.35 319.15
PHILADELPHIA TOWER
118.5 327.05
(Rwys 9L/27R, 8/26 and 17/35)
135.1 327.05
(Rwy 9R/27L)
GND CON
121.9 348.6

RADAR REQUIRED
Weather Minimums: 3000'
ceiling and 7 mile visibility.

RADAR REQUIRED

Weather Minimums: 3000' ceiling and 7 mile visibility.

1 NM	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
------	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----

LIBERTY VISUAL RWY 27L

Expect RADAR vectors to the MXE R-107.

Proceed Northwest on the MXE R-107 inbound for Rwy 27L.

Report the airport in sight to final controller.

Aircraft must remain on the MXE R-107 until the MXE R-107/27 DME; then proceed visually to Rwy 27L or as assigned by the tower.

Expect aircraft to be utilizing a simultaneous visual or ILS approach to Rwy 27R during this operation.

LIBERTY VISUAL RWY 27L

Orig 23APR98

39°52'N-75°14'W

PHILADELPHIA, PENNSYLVANIA
PHILADELPHIA INTL (PHL)