


WAAS CH 53531 W26A	APP CRS 260°	Rwy Ldg 10496 TDZE 4659 Apt Elev 4729
--	------------------------	--


RNAV (GPS) RWY 26L

PUEBLO MEML (PUB)

RNP APCH-GPS.				MISSED APPROACH: Climb to 7000 direct MERTZ and hold.		
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C.						
ATIS 125.25	DENVER APP CON ★ 120.1 290.5		PUEBLO TOWER ★ 119.1 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 120.9	UNICOM 122.95



ELEV 4729	D	TDZE 4659
-----------	----------	-----------



7000 MERTZ

*RNAV only

RW26L

1.4 NM

JIKTA

4.5 NM

6600

HELER

6 NM Holding Pattern

080° → 7000

← 260°

GP 3.00°
TCH 60

CATEGORY	A	B	C	D
LPV DA		4859-3 ³ / ₄	200 (200-3 ³ / ₄)	
LNAV/VNAV DA		4979-1	320 (300-1)	
LNAV MDA	5100-1	441 (400-1)	5100-1 ³ / ₈	441 (400-1 ³ / ₈)
CIRCLING	5340-1	611 (700-1)	5580-2 ¹ / ₂ 851 (900-2 ¹ / ₂)	5800-3 1071 (1100-3)