

APP CRS
336°

Rwy Ldg
TDZE
1160

Apt Elev
1175

RNAV (RNP) Z RWY 34

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

RNP AR APCH. RF required.

⚠

Missed approach requires RNP less than 1.0. For inop ALS, increase RNP 0.30* all Cats visibility to 1½ SM.

❄-12°C

Inop table does not apply to RNP 0.30.

For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C.

MALSR

AS

MISSED APPROACH: Climb to 6000 on track 336° to DMOSS, right turn to SETHB, right turn to JEEVY and on track 093° to PROSE and hold. * Missed approach requires minimum climb of 350 feet per NM to 4100. # Missed approach requires minimum climb of 415 feet per NM to 4100.

ATIS 132.375	ROANOKE APP CON 133.225 339.8	ROANOKE TOWER 118.3 257.8	GND CON 121.9 257.8
------------------------	---	-------------------------------------	-------------------------------

ELEV 1175

D

TDZE 1160

6000

DMOSS

SETHB

JEEVY

PROSE

tr 336°

See planview for multiple IF locations.

NAVBE 3800

GP 3.00°

TCH 56°

CATEGORY	A	B	C	D
RNP 0.15 DA #	1495-½	335 (400-½)		
RNP 0.30 DA*	1646-1	486 (500-1)		
RNP 0.30 DA	2115-4	955 (1000-4)		

AUTHORIZATION REQUIRED

ROANOKE, VIRGINIA

Orig 15AUG19

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

37°20'N-79°59'W

RNAV (RNP) Z RWY 34

NE-3, 01 OCT 2026 to 29 OCT 2026

NE-3, 01 OCT 2026 to 29 OCT 2026